

**Material Safety Data Sheet**

For chemicals, coatings, and related materials  
In compliance with OSHA 29 CFR 1910.1200

Date Prepared:  
01-31-15

NAME: Delta Polymers, Inc.  
ADDRESS: 130 South 2<sup>nd</sup> Street  
CITY/STATE: North Bay Shore, New York  
ZIP CODE: 11706

INFORMATION PHONE NOS.  
DAY: (631) 595-2530  
FAX: (631) 595-2537  
EMERGENCY PHONE #: (800) 486-3512

Section I – Product

NAME: Polybond 1030 – Part A  
CLASS: Epoxy Resin

HMIS HAZARD CODES  
Health: 2 (Moderate)  
Flammability: 1 (Slight)  
Reactivity: 0 (Minimal)

Personal Protective Equipment: H

Section II – Hazardous Ingredients

---Ingredient---	Percent	C.A.S. Registry	LEL	Vapor Pressure
Material Description	by Weight			mm Hg @ 20°C
Liquid Epoxy Resin	78	*Trade Secret	n/a	0.99
Graded Sand	15	*Trade Secret	n/a	n/a
Solvents	7%	*Trade Secret	n/a	n/a

Section III – Physical Data

Boiling Range: n/a                      Freezing Point: n/a  
Vapor Pressure: n/a mm@20°C              Vapor Density: n/a  
Specific Gravity: 1.20                      H<sub>2</sub>O Solubility: Negligible (< 0.1%)  
Evaporation Rate: Slower                      % Volatile by Volume: n/a %  
(Relative to n-butyl acetate)

Appearance and Odor: Clear/Neutral Liquid (gel) , Slight Odor.

Section IV – Fire and Explosion Hazard Data

Flash point: 350°F              Explosive Limits:              LEL              UEL (%V in air)  
(Method used) Pensky-Martens              n/a              n/a

Flammability Classification

OSHA: Combustible Liquid – Class III B

DOT: Not regulated

Extinguishing Media:

Water Fog, Foam, Carbon Dioxide (CO<sub>2</sub>), Dry Chemical

Special Fire Fighting Procedures:

Use water fog to cool containers.

Wear protective clothing.              Fight fire from a safe distance.

Close all valves to the area.              Shut off all power to the area.

Emergency lights must be turned on.

Self-contained breathing apparatus is to be used.

Under fire conditions irritating and/or toxic gases may be present.

Unusual Fire and Explosion Hazards: None

Section V - Toxicological Information

---Ingredient---	OSHA	ACGIH	LD50 (mg/kg)		LC50 (ppm)	
Material Ingredient	PEL	TLV (twa)	(rat)	(rbt)	(rat)	
		Mg/m3	ppm	oral	dermal	inhal
Liquid Epoxy Resin	n/a	n/a	n/a	11400	20001	n/a

Section VI - Health Hazard Data

Effects of Overexposure: Threshold Limit Values: See Section V.

- Vapors may irritate the eyes and respiratory tract.
- Contact irritating to eyes and moderately irritating to skin.
- May cause skin sensitization and other allergic responses.
- May aggravate an existing dermatitis.

Emergency and First Aid Procedures:

- Move to fresh air. Apply artificial respiration, if necessary.
- Wash skin with soap and water or waterless hand cleaners.
- Remove contaminated clothing.
- Induce vomiting.
- Drink large quantities of water immediately.
- Flush Eyes with water for 15 minutes, and get medical attention.
- If breathing is difficult, oxygen may be given.

Section VIII - Reactivity Data

Stability: Stable

Stability Conditions to Avoid: None.

Incompatibility (Materials to Avoid Contact With):

- Strong oxidizing agents and mineral acids.

Hazardous Decomposition Products:

- Oxides of carbon and aldehydes.
- Toxic monomer fumes and/or short chain hydrocarbons.

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None.

Section VIII - Spill or Leak Procedures

Steps For Material Spillage:

- Absorb with sand and dispose of in an approved manner.
- Dike area with sand to contain spilled liquid.
- Prevent spillage from entering underground water systems.
- Ventilate area. Flush area with water but do NOT flush into sewer.
- Remaining material may be emulsified with soap and water and absorbed.
- Scoop up contaminated soil and place in dry drums.
- Large spills may be pumped into closed, but not sealed containers.

Waste disposal methods:

- Empty decontaminated containers should be crushed to prevent reuse.
- Dispose of in accordance with local regulations.

Section IX - Special Protection Information

Respiratory protection:

NESA/NIOSH approved respirator is highly recommended.  
Self-contained breathing apparatus in concentrations above PEL/TLV.

\*\*Avoid breathing mists, vapors, or fumes which can cause severe respiratory damage.

\*\*Always work in areas with adequate ventilation to allow dissipation of vapors.

Ventilation:

Provide adequate cross air circulation.

Protective Gloves:

Gloves resistant to chemical penetration  
Rubber or Neoprene Gloves.

Eye Protection:

Splashproof safety, Chemical Worker and Chemical Splash goggles.

Other Protective Equipment:

Eyewash Station, Emergency Shower, and use of barrier cream recommended.  
Chemical Apron, Rubber foot covering, clean long sleeve and leg clothing.

Section X - Special Precautions

Handling and Storage Precautions:

Store in a cool dry place. Keep away from open flames.  
Store in tightly closed containers Store away from food and beverages.  
Wash thoroughly after handling.  
Wash before eating, drinking, smoking, or using toilet.

Other Precautions:

Check all containers for leaks.  
Avoid prolonged breathing or contact with skin.

Proprietary Ingredient - may be made available as provided in 29 CFR 1910.1200 (I).

\*\*\*Product contains Epoxy Resin that may contain ECH at 2-3 ppm.\*\*\*

Reportable under SARA Title III Chemical	Percent	CAS	Sections: 313	302 TPQ (#)	304 RQ (#)
Epichlorohydrin	2-3 ppm	000106-89-8	Y		1000

AUTHORIZED SIGNATURE: R.A. Rana Chemist